
Presence detector - Professional Line



BT IPD (Slave) - surface EAN 4007841 064426 Article number 064426







Function description

Smart surveillance professional. The HF 360-2 from the new Control PRO 2 range. Modern look and intelligent 360° HF sensor technology – ideal for stairwells and toilet facilities with cubicles. Conveniently adjusted and interconnected via Bluetooth. Interfaces: COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave). Mounting height up to 3.5 m. Reach: 12 m.

Technical specifications

Туре	Presence detector
Dimensions (L x W x H)	57 x 123 x 123 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Power consumption	0,5 W
Sensor Technology	High frequency
Application, place	Indoors
Installation site	ceiling
Installation	Surface wiring
Mounting height	2,50 – 4,00 m
Reach, radial	Ø 12 m (113 m²)
Reach, tangential	Ø 12 m (113 m²)
Reach, detail	1 or 2 detection directions can be masked out by stickers for adjustment to the room situation.
HF-system	5,8 GHz
Detection angle	360 °
Angle of aperture	140 °
Optimum mounting height	2,8 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	No

Electronic scalability	Yes
Detection	also through glass, wood and stud walls
Twilight setting TEACH	No
Constant-lighting control	No
Basic light level function	No
Settings via	Bluetooth
With remote control	No
Interconnection	Yes
Type of interconnection	Master/slave
IP-rating	IP54
Material	Plastic
Ambient temperature	-25 – 50 °C
Application, room	function room / ancillary room, kitchenette, stairwell, WC / washroom, Indoors
Colour	white
Colour, RAL	9003
Manufacturer's Warranty	5 years
Version	BT IPD (Slave) - surface
PU1, EAN	4007841064426


Presence detector - Professional Line



BT IPD (Slave) - surface EAN 4007841 064426 Article number 064426



Detection Zone



Mögliche Montagehöhe: 2,50 m – 4,00 m Orange: radial und tangential

Circuit diagram



