
#### Sensor-switched LED outdoor light

### L 260 LED

EAN 4007841 007874 Article number 007874







LED

3000 K

 $(\bigcirc)$ 

<u>~;</u>

IP44

- 4h -



#### **Function description**

The classic sensor. Now even more economical. STEINEL sensor-switched outdoor light L 260 LED, ideal for building entrances, fronts of buildings, patio and side areas. 8,6 W STEINEL LED lamp, 700 lm, 240° infrared sensor, 12 m reach, high-quality stainless steel with opal glass shade.

#### Sensor-switched LED outdoor light

## L 260 LED

EAN 4007841 007874 Article number 007874



#### **Technical specifications**

Dimensions (L x W x H)	177 x 102 x 426 mm
Mains power supply	230 – 240 V / 50 Hz
Mounting height max.	6,00 m
Sensor Technology	passive infrared
Output	8,6 W
Interconnection	No
Slave modeselectable	No
Luminous flux	700 lm
Efficiency	81 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index	80-89
With lamp	Yes, LED lamp
Lamp	LED can be replaced
LED life expectancy (max. °C)	25000 h
Base	E27
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection angle	240 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes

Electronic scalability	No
Mechanical scalability	No
Reach, radial	r = 6 m (75 m²)
Reach, tangential	r = 12 m (302 m <sup>2</sup> )
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 Min.
Basic light level function	No
Soft light start	Yes
Continuous light	selectable, 4h
Impact resistance	IK03
IP-rating	IP44
Protection class	I
Ambient temperature	-20 – 50 °C
Housing material	Stainless steel
Cover material	Glass opal
Manufacturer's Warranty	3 years
Settings via	Potentiometers
With remote control	No
Cover material	shrouds
PU1, EAN	4007841007874

#### Accessories

EAN 4007841 008314	LED linear lamp for L 260 LED
EAN 4007841 001353	Replacement glass shade for L 260 S


#### Sensor-switched LED outdoor light

# L 260 LED

EAN 4007841 007874 Article number 007874



#### **Detection Zone**



Mögliche Montagehöhe: 1,80 m - 6,00 m

Orange: radial Schwarz: tangential

### **Dimension Drawing**

