

Photo-cell controller

# NightMatic 2000

black

EAN 4007841 550318

Article number 550318



Twilight switch

1000 W

1000 W max.  
(LED-ready)



IP54



2 - 30 lux



energy saving

3 years

manufacturer's  
warranty  
steinel.de/garantie



CE



TÜV Nord  
Baumuster  
checked

## Function description

Automatic illumination. Photo-electric lighting controller NightMatic 2000, for controlling lighting systems for building fronts, properties, shop windows etc., automatically switches light 'ON' at dusk automatically 'OFF' again at dawn.

## Technical specifications

Type	Photo-cell controller	Constant-lighting control	No
Dimensions (L x W x H)	37 x 74 x 99 mm	Basic light level function	No
Mains power supply	230 – 240 V / 50 Hz	Settings via	Potentiometers
Power consumption	0,8 W	Interconnection	Yes
Sensor Technology	Light sensor	Type of interconnection	Master/master
Application, place	Outdoors	IP-rating	IP54
Installation site	wall	Material	Plastic
Installation	Surface wiring	Ambient temperature	-20 – 50 °C
Twilight setting TEACH	Yes	Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Twilight setting	2 – 30 lx	Colour	black
Switching output 1, resistive	1000 W	Colour, RAL	9005
Switching output 1, number of LEDs / fluorescent lamps	4 pcs.	Manufacturer's Warranty	3 years
Fluorescent lamps, uncorrected	500 VA	Version	black
Capacitive load in µF	88 µF	PU1, EAN	4007841550318

Photo-cell controller

# NightMatic 2000

black

EAN 4007841 550318

Article number 550318



## Dimension Drawing

