
Multisensor - Professional Line

Multisensor Air KNX

V3.0 EAN 4007841 056346 Article number 056346







Function description

Multisensor AIR KNX, the air, brightness and temperature specialist. Multisensor Air KNX delivers reliable additional information to the building management system. It measures temperature, humidity, air pressure, volatile organic compounds (VOC), CO2 concentration as well a brightness. Without True Presence® detection. But geared towards the design if the True Presence family. For a modern ceiling look all round. KNX interface for easy integration.

Technical specifications

Dimensions (L x W x H)33 x 123 x 123 mmMains power supply30 VPower consumption0,5 WPower supply, detailKNX busSensor TechnologyMultisensorApplication, placeIndoorsInstallation siteceilingInstallationConcealed wiringMounting height2,8 mTwilight setting TEACHYesTwilight setting controlNo	Туре	Other
Power consumption0,5 WPower supply, detailKNX busSensor TechnologyMultisensorApplication, placeIndoorsInstallation siteceilingInstallationConcealed wiringMounting height4,00 mOptimum mounting height2,8 mTwilight setting TEACHYesTwilight setting2 – 1000 lx	Dimensions (L x W x H)	33 x 123 x 123 mm
Power supply, detailKNX busSensor TechnologyMultisensorApplication, placeIndoorsInstallation siteceilingInstallationConcealed wiringMounting height4,00 mOptimum mounting height2,8 mTwilight setting TEACHYesTwilight setting2 – 1000 lx	Mains power supply	30 V
Sensor TechnologyMultisensorApplication, placeIndoorsInstallation siteceilingInstallationConcealed wiringMounting height4,00 mOptimum mounting height2,8 mTwilight setting TEACHYesTwilight setting2 – 1000 lx	Power consumption	0,5 W
Application, placeIndoorsInstallation siteceilingInstallationConcealed wiringMounting height4,00 mOptimum mounting height2,8 mTwilight setting TEACHYesTwilight setting2 – 1000 lx	Power supply, detail	KNX bus
Installation siteceilingInstallationConcealed wiringMounting height4,00 mOptimum mounting height2,8 mTwilight setting TEACHYesTwilight setting2 – 1000 lx	Sensor Technology	Multisensor
InstallationConcealed wiringMounting height4,00 mOptimum mounting height2,8 mTwilight setting TEACHYesTwilight setting2 – 1000 lx	Application, place	Indoors
Mounting height4,00 mOptimum mounting height2,8 mTwilight setting TEACHYesTwilight setting2 – 1000 lx	Installation site	ceiling
Optimum mounting height2,8 mTwilight setting TEACHYesTwilight setting2 – 1000 lx	Installation	Concealed wiring
Twilight setting TEACHYesTwilight setting2 - 1000 lx	Mounting height	4,00 m
Twilight setting 2 – 1000 lx	Optimum mounting height	2,8 m
	Twilight setting TEACH	Yes
Constant-lighting control No	Twilight setting	2 - 1000 lx
	Constant-lighting control	No
Basic light level function Yes	Basic light level function	Yes

KNX functions	Comfort, CO2, Light level, HVAC output, Air pressure, Humidity output, Dewpoint, Temperature output, VOC, Photo-cell controller, Logic gate
With bus coupling	Yes
Settings via	ETS software, Bluetooth, Bus
With remote control	No
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
IP-rating	IP20
Material	Plastic
Ambient temperature	0-40 °C
Application, room	classroom, lecture hall, one-person office, open-plan office, conference room / meeting room, hotel room, care room, duty room, recreation room, sports hall, reception / lobby, Indoors
Colour	white
Colour, RAL	9016
Manufacturer's Warranty	5 years
PU1, EAN	4007841056346

Multisensor - Professional Line

Multisensor Air KNX

V3.0 EAN 4007841 056346 Article number 056346



Accessories

EAN 4007841 063870

Surface-mounting adapter for Multisensor

Detection Zone

Dimension Drawing

