Spot Garden

Sensor Connect
EAN 4007841 058685
Article number 058685

.steinel

LED	3000 K									
20.000 h	3000K warm-white	38°	infrared sensor 90°	max. 10 m	IP44	2 - 2000 lux (via App)	5 sec - 60 min (via App)	manual override 4h	energy saving

Function description

Interconnected garden enjoyment. The Spot Garden Sensor Connect ground spotlight with 90° infrared sensor simply pushes into the earth and provides versatile illumination all around the home. The LED spot is conveniently set, interconnected and controlled via Bluetooth by app. ON and OFF times, twilight and time settings as well as creating lighting group – all not a problem. 520 lm, 7 W, 3000 K. Includes 2.5 m mains plug and GU-10 LED.

Technical specifications

Dimensions (L x W x H)	140 x 69 x 369 mm		Photo-cell controller	Yes
Mains power supply	220 – 240 V / 50 – 60 Hz		Twilight setting	2 – 2000 lx
Sensor Technology	passive infrared		Time setting	5 s – 60 Min.
Output	7 W		Basic light level function	No
Power consumption	0,5 W		Main light adjustable	No
Interconnection	Yes		Functions	Digital timer, Master/slave override
Slave modeselectable	Yes		Settings via	Bluetooth
Luminous flux	520 lm		Soft light start	No
Colour temperature	3000 K		Continuous light	selectable, 4h
Colour variation LED	SDCM5		Impact resistance	IK03
Colour Rendering Index	80-89		IP-rating	IP44
With lamp	Yes, LED lamp		Protection class	II
Lamp	LED can be replaced		Ambient temperature	-20 – 40 °C
With motion detector	Yes		Housing material	Aluminium
Detection angle	90 °		Cover material	Plastic, transparent
Angle of aperture	90 °		Manufacturer's Warranty	3 years
Sneak-by guard	No		Includes corner wall mount	No
Capability of masking out individual segments	No		PU1, net weight	0,71 kg
Reach, radial	r = 2 m (3 m²)		Version	Sensor Connect
Reach, tangential	r = 10 m (79 m²)		PU1, EAN	4007841058685

.● steinel

Detection Zone

2 m

10 m

Mögliche Montagehöhe: –
Orange: radial
Schwarz: tangential

Dimension Drawing

369

69

118