

Light Sensor Dual

V3 KNX - concealed, sq.
 EAN 4007841 058326
 Article number 058326



Twilight switch +
eco-mode



KNX



IP20



2 - 1000 lux



max 4 m



CE

5 years

manufacturer's
warranty
steinel-professional.de/garantie

Function description

Light measurement in perfection. The Light Sensor Dual photo-cell controller with KNX interface measures directed and diffuse light, watches over areas below the sensor and measures the room brightness. Combining the measurement results reduces error influences. Available either in round or square surface-mounted and concealed version.

Technical specifications

Type	Constant-lighting controller	With bus coupling	Yes
Dimensions (L x W x H)	51 x 94 x 94 mm	Settings via	ETS software, Remote control, Bus, Smart Remote
Power supply, detail	KNX bus	Interconnection	Yes
Sensor Technology	Light sensor	Type of interconnection	Master/master, Master/slave
Application, place	Outdoors, Indoors	IP-rating	IP20
Installation site	wall, ceiling	Ambient temperature	-20 – 50 °C
Installation	Concealed wiring	Application, room	classroom, one-person office, open-plan office, high-bay warehouse, conference room / meeting room, Indoors
Mounting height	2,00 – 4,00 m	Colour	white
Twilight setting TEACH	Yes	Colour, RAL	9003
Twilight setting	2 – 1000 lx	Manufacturer's Warranty	5 years
Constant-lighting control	Yes	Version	KNX - concealed, sq.
Basic light level function	Yes	PU1, EAN	4007841058326
KNX functions	Light output 2x, Light level, Constant-lighting control, Photo-cell controller, Logic gate		

Photo-cell controller - Professional Line

Light Sensor Dual

V3 KNX - concealed, sq.
EAN 4007841 058326
Article number 058326



Dimension Drawing

